

---

# EST 1000/2

## EVO-SPORT SEAMING TAPE

---

### PRODUCT DESCRIPTION & USE

Evo-Sport EST 1000/2 is a specially constructed tape for use with Evo-Sport adhesives in forming strong bonds when seam jointing artificial sand-filled carpets used in the surfacing of sports pitches.

The tape consists of a strong geo-textile fabric laminated to a polyolefin backing film designed to prevent the penetration of adhesive through to the under surface.

### FEATURES

- Film backed to prevent adhesive penetrating to base
- Strong rot proof geo-textile bonding medium
- Lays flat to substrate when rolled out
- Impervious to moisture ingress from the base
- Backing film easily removed for cross over joints

### TECHNICAL DATA

<b>Colour &amp; Form</b>	White geo-textile / transparent film.
<b>Bonding Medium</b>	Non-woven polyester geo-textile.
<b>Backing Medium</b>	Modified polyolefin film.
<b>Roll Size</b>	Length: 300 metres. Width: 300 mm, 400 mm and 500 mm. Thickness: 0.8 mm.
<b>Weight</b>	170 grams per square metre.
<b>Tensile Strength</b>	400 N/50 mm.
<b>Temperature Stability</b>	- 25°C to + 70°C.
<b>Storage</b>	Store in dry conditions within temperature range + 5°C to + 30°C.
<b>Packaging</b>	Rolls individually film wrapped.

### MATERIAL SAFETY DATA

Before starting work using EST 1000/2 the separate Material Safety Data Sheet must be studied carefully by those carrying out the work.

### APPLICATION

EST 1000/2 is designed for use with Evo-Sport 9604, Evo-Sport 7174 and Evo-Sport 2000 All Weather Adhesive. It is constructed to form strong bonds to artificial sand filled carpets when used with these adhesives. The correct amount of Evo-Sport adhesive is applied by notched trowel to the fabric side of the tape and the edges of the carpet are pressed into the wet adhesive.

See more detailed instructions on Product Data Sheets for Evo-Sport 9604 and Evo-Sport 7174.

---

This Product Data Sheet covers just one of a large range of products supplied by Bostik Limited. Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This Product Data Sheet supersedes all previous technical information on this product, and users of it are cautioned to ensure that it is the current issue. Destroy all previous Product Data Sheets, and if any doubt, contact Bostik Limited, quoting the code number in the top right hand corner on the front of this document. This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.